


Indian Standard

CODE OF PRACTICE FOR
INSTALLATION AND OPERATION OF
SINGLE POINT HYDRAULIC
OVER-FLOW SETTING GAUGE

UDC 681.128:681.121.873:006.76



© Copyright 1986

INDIAN STANDARDS INSTITUTION
MANAK BHAVAN, 9 BAHADUR SHAH ZAFAR MARG
NEW DELHI 110002

Indian Standard

CODE OF PRACTICE FOR INSTALLATION AND OPERATION OF SINGLE POINT HYDRAULIC OVER-FLOW SETTING GAUGE

Foundation Engineering Sectional Committee, BDC 43

Chairman

MAJ-GEN OMBIR SINGH

Representing

Ministry of Defence

Members

COL K. P. ANAND (<i>Alternate</i> to Maj-Gen Ombir Singh)	Ministry of Railways (RDSO)
ADDITIONAL DIRECTOR (GE)	Ministry of Railways (RDSO)
ADDITIONAL DIRECTOR (S) (<i>Alternate</i>)	
SHRI K. K. AGGARWAL	Posts & Telegraph Department, New Delhi
SHRI B. ANJIAH	A.P. Engineering Research Laboratories, Hyderabad
SHRI ARJUN RIJHSINGHANI	Cement Corporation of India, New Delhi
SHRI O. S. SRIVASTAVA (<i>Alternate</i>)	
DR R. K. BHANDARI	Central Building Research Institute (CSIR), Roorkee
SHRI CHANDRA PRAKASH (<i>Alternate</i>)	
SHRI MAHABIR BIDASARIA	Ferro-Concrete Consultants Pvt Ltd, Indore
SHRI ASHOK BIDASARIA (<i>Alternate</i>)	
SHRI S. P. CHAKRABARTI	Ministry of Transport (Roads Wing)
SHRI P. K. DUTTA (<i>Alternate</i>)	
SHRI A. K. CHATTERJEE	Gammon India Ltd, Bombay
SHRI A. C. ROY (<i>Alternate</i>)	
CHIEF ENGINEER	Calcutta Port Trust, Calcutta
SHRI S. GUHA (<i>Alternate</i>)	
SHRI R. K. DAS GUPTA	Simplex Concrete Piles (I) Pvt Ltd, Calcutta
SHRI H. GUHA BISWAS (<i>Alternate</i>)	
SHRI A. G. DASTIDAR	In personal capacity (5 Hungerford Court, 121 Hungerford Street, Calcutta)
SHRI V. C. DESHPANDE	Pressure Piling Co (I) Pvt Ltd, Bombay
DIRECTOR (CSMRS)	Central Soil and Materials Research Station, New Delhi
CHIEF RESEARCH OFFICER (CSMRS) (<i>Alternate</i>)	

(Continued on page 2)

© Copyright 1986

INDIAN STANDARDS INSTITUTION

This publication is protected under the *Indian Copyright Act* (XIV of 1957) and reproduction in whole or in part by any means except with written permission of the publisher shall be deemed to be an infringement of copyright under the said Act.

(Continued from page 1)

<i>Members</i>	<i>Representing</i>
SHRI A. H. DIVANJI	Asia Foundations and Construction Private Limited, Bombay
SHRI A. N. JANGLE (<i>Alternate</i>)	
SHRI A. GHOSHAL	Stup Consultants Limited, Bombay
DR GOPAL RANJAN	University of Roorkee, Roorkee
SHRI N. JAGANNATH	Steel Authority of India Ltd, Durgapur
SHRI A. K. MITRA (<i>Alternate</i>)	
SHRI ASHOK K. JAIN	G. S. Jain & Associates, New Delhi
SHRI VIJAY KUMAR JAIN (<i>Alternate</i>)	
JOINT DIRECTOR (DESIGN)	National Buildings Organization, New Delhi
SHRI SUNIL BERY (<i>Alternate</i>)	
DR R. K. KATTI	Indian Institute of Technology, Bombay
SHRI S. R. KULKARNI	M. N. Dastur & Company Pvt Ltd, Calcutta
SHRI S. ROY (<i>Alternate</i>)	
SHRI A. P. MATHUR	Central Warehousing Corporation, New Delhi
SHRI V. B. MATHUR	Mackenzies Ltd, Bombay
SHRI S. MUKHERJEE	In personal capacity (<i>E-104 A, Simla House, Nepean Sea Road, Bombay</i>)
SHRI T. K. D. MUNSI	Engineers India Limited, New Delhi
SHRI M. IYENGAR (<i>Alternate</i>)	
SHRI A. V. S. R. MURTY	Indian Geotechnical Society, New Delhi
SHRI B. K. PANTHAKY	Hindustan Construction Co Ltd, Bombay
SHRI V. M. MADGE (<i>Alternate</i>)	
SHRI M. R. PUNJA	Cemindia Company Ltd, Bombay
SHRI D. J. KETKAR (<i>Alternate</i>)	
DR V. V. S. RAO	Nagadi Consultants Private Limited, New Delhi
DR A. SARGUNAN	College of Engineering, Guindy, Madras
SHRI S. BOMMINATHAN (<i>Alternate</i>)	
SUPERINTENDING ENGINEER (DESIGNS)	Central Public Works Department, New Delhi
EXECUTIVE ENGINEER (DESIGNS V) (<i>Alternate</i>)	
DR A. VARADARAJAN	Indian Institute of Technology, New Delhi
DR R. KANIRAJ (<i>Alternate</i>)	
SHRI G. RAMAN, Director (Civ Engg)	Director General, ISI (<i>Ex-officio Member</i>)

Secretary

SHRI K. M. MATHUR
Joint Director (Civ Engg), ISI

Foundation Instrumentation Subcommittee, BDC 43:7

Convener

DR R. K. BHANDARI Central Building Research Institute (CSIR), Roorkee

Members

SHRI K. N. BARTAR Pie Roorkee (India), Roorkee
SHRI M. IYENGAR Engineers India Ltd, New Delhi
DR R. K. M. BHANDARI (*Alternate*)

(Continued on page 7)

Indian Standard

CODE OF PRACTICE FOR INSTALLATION AND OPERATION OF SINGLE POINT HYDRAULIC OVER-FLOW SETTING GAUGE

0. FOREWORD

0.1 This Indian Standard was adopted by the Indian Standards Institution on 30 January 1986, after the draft finalized by the Foundation Engineering Sectional Committee had been approved by the Civil Engineering Division Council.

0.2 Hydraulic over-flow settlement gauge is a simple device used for measuring settlements of earthfill like ground; embankments and dams. This standard is being formulated so as to cover detail guidance in regard to installation and operation of such single point type of gauge which is commonly used.

0.3 For the purpose of deciding whether a particular requirement of this standard is complied with, the final value, observed or calculated, expressing the result of a test or analysis, shall be rounded off in accordance with IS: 2-1960*. The number of significant places retained in the rounded off value should be the same as that of the specified value in this standard.

1. SCOPE

1.1 This standard covers details of installation and operation of single point hydraulic over-flow settlement gauge.

2. GENERAL

2.1 Hydraulic over-flow settlement gauge is essentially a instrument which works on the principle of manometer and is thus basically a large U-tube. Its one end is in the form of a measuring stand pipe (manometer) located in a remotely built instrument house and the other end is an over-flow tube terminating in the settlement capsule.

*Rules for rounding off numerical values (*revised*).

2.2 The unit comprises (a) a cylindrical settlement capsule (cell) of glass/Pvc (b) a rigid transparent measuring glass/Pvc stand pipe which shall a metre high and (c) a set of three Pvc/glass tubes that is drain tube, air line tube and water over-flow tube with brass leak proof connections. Each of these tubes shall be not less than 30 m long (*see* Fig. 1).

3. INSTALLATION AND OPERATION (*see* Fig. 1)

3.1 The three tubes should be connected at the appropriate junctions at the bottom of the settlement cell through leak proof connections and the cell should be installed vertically within the fill or the subgrade at the elevation where measurements are required. The cell should then be encased in concrete. The tubings from the cell should be laid in a shallow trench leading to the instrument house. In order to assist quick drainage of the water from the cell, a minimum longitudinal slope of 1 in 100 should be provided in trench bottom towards instrument house. The tubings should be coated with minimum 50 mm thick bentonite layer of working consistency and the trench backfilled with sand or soil to avoid stones damaging the tubes. A reference level is marked on the outside of each gauge in order to check the initial reading.

3.2 The height of the stand pipe should be selected so as to cover up the elevation of the cell unit and its anticipated settlement.

3.3 When the centre of the scale of the stand pipe is at the same level as the upper end of the over-flow tube in the settlement cell, the air pressure acting on both is the same. The elevation of the over-flow level in the cell is then read out on the scale attached to the stand pipe.

3.4 If it is not possible to have the buried settlement cell and the stand pipe at the same level, the air pressure in the stand pipe can be increased or reduced by a column of water. At rest (stabilization), the water level stands in the stand pipe lowered or raised by exactly the height of the additional water column.

3.5 The gauge should have an accuracy of ± 1 mm when the stand pipe is at the same height as the cell and ± 2 mm when the water column is used.

4. PROCEDURE

4.1 The system is primed by passing de-aired water from the read-out location to the cell via the water tube, and back through the drain tube. This circulation should be continued until all air has been removed from the water tube.

4.2 The water supply valve is then closed, and air pressure applied to the top of the cell through the air line. All water, except that in the cylinder and water tube should be expelled and a continuous stream of air should be noted at the read out station through the drain tube.

4.3 The water level in the cell should then be at *A* as shown in Fig. 1 and the cell should be at the atmospheric pressure through the air tube. This level is noted in the stand pipe after connecting the same to the cell and adjusting it to the stabilized point.

4.4 Any subsequent settlement of the strata should cause a corresponding settlement of the cell, thus causing a variation in the level of the water column in the stand pipe. The changed level should be recorded after making necessary adjustments. The difference between initial and final levels of stand pipe water column level indicates the settlement at the level of the cell.

5. PRECAUTIONS

5.1 Before taking measurements, the over-flow tube should be de-aired. If necessary, a slight suction may be applied through the drain tube to facilitate drainage of the over-flow water. To take care of the effect of temperature of water, it should be flushed with de-aired water before each measurement is taken.

5.2 All connections should be ensured to be leak-proof and a pair of spanners should be used to screw and unscrew the compression couplings.

5.3 The measuring unit should be installed outside the zone affected by settlement.

5.4 As the air tube has to maintain the over-flow and the stand pipe water surfaces at the same pressure it should be kept free from all kinds of obstructions such as water droplets and other such obstructions.




FIG. 1 DETAILS OF INSTALLATION OF SINGLE POINT HYDRAULIC SETTLEMENT GAUGE

(Continued from page 2)

Members

SHRI Z. M. KARACHIWALA

DR B. V. K. LAVANIA

SHRI P. K. NAGARKAR

SHRI M. K. KULKARNI (*Alternate*)

SHRI M. D. NAIR

SHRI A. V. SHASTRI (*Alternate*)

DR N. V. NAYAK

SHRI N. K. OZA

SHRI V. M. SHARMA

PROF N. SOM

Representing

Vasi Shums & Co Pvt Ltd, Bombay

University of Roorkee, Roorkee

Maharashtra Engineering Research Institute, Nasik

Associated Instrument Mfrs (I) Pvt Ltd, New Delhi

Asia Foundations & Constructions Ltd, Bombay

Ministry of Railways (RDSO)

Central Soil and Materials Research Station,
New Delhi

Jadavpur University, Calcutta

INTERNATIONAL SYSTEM OF UNITS (SI UNITS)

Base Units

<i>Quantity</i>	<i>Unit</i>	<i>Symbol</i>
Length	metre	m
Mass	kilogram	kg
Time	second	s
Electric current	ampere	A
Thermodynamic temperature	kelvin	K
Luminous intensity	candela	cd
Amount of substance	mole	mol

Supplementary Units

<i>Quantity</i>	<i>Unit</i>	<i>Symbol</i>
Plane angle	radian	rad
Solid angle	steradian	sr

Derived Units

<i>Quantity</i>	<i>Unit</i>	<i>Symbol</i>	<i>Definition</i>
Force	newton	N	1 N = 1 kg · m/s ²
Energy	joule	J	1 J = 1 N · m
Power	watt	W	1 W = 1 J/s
Flux	weber	Wb	1 Wb = 1 V · s
Flux density	tesla	T	1 T = 1 Wb/m ²
Frequency	hertz	Hz	1 Hz = 1 c/s (s ⁻¹)
Electric conductance	siemens	S	1 S = 1 A/V
Electromotive force	volt	V	1 V = 1 W/A
Pressure, stress	pascal	Pa	1 Pa = 1 N/m ²